



Fast Ethernet PCI Network Card

Get up to speed in a snap!

The INTELLINET NETWORK SOLUTIONS™ Fast Ethernet PCI Network Card is a high-performance network adapter designed to fit into the PCI slot of your desktop computer. It allows you to upgrade your computer to support Fast Ethernet network speeds, providing 10 times the speed of 10Base-T Ethernet.

Faster Throughput

The Fast Ethernet PCI Network Card supports throughput rates of up to 200 Mbps when running in full duplex mode. This is ideal for resource intensive CAD/CAM, client-server database, multimedia, pre-press, advertising graphics, server and mission-critical applications.

Auto Negotiation

The Fast Ethernet PCI Network Card will automatically detect the network speed that the LAN switch port is set to and run at the same speed. The card supports 10Base-T Ethernet and 100Base-TX Fast Ethernet.

Full Duplex

When running in full duplex mode, the Fast Ethernet PCI Network Card provides the following throughput rates: 20 Mbps (10Base-T Ethernet) and 200 Mbps (100Base-TX Fast Ethernet).

Lifetime Warranty

Strict manufacturing standards ensure the highest quality in all INTELLINET NETWORK SOLUTIONS products. All items carry a full Lifetime Warranty — the strongest quality commitment anyone can make.

Model
509510





Model
509510

Features

- Supports 10/100 speeds over Cat5e network cable
- Supports 32-bit PCI V2.1
- Full duplex speeds (20 Mbps, 200 Mbps)
- Auto-negotiation with next page capability
- Full duplex flow control (IEEE 802.3x)
- Lifetime Warranty

Specifications

NETWORK

- IEEE 802.3 (10Base-T Ethernet)
- IEEE 802.3u (100Base-TX Fast Ethernet)
- RJ-45 Connector
- MDI/MDI-X
- Ethernet 10 Mbps (half-duplex)
- Ethernet 20 Mbps (full-duplex)
- Fast Ethernet 100 Mbps (half-duplex)
- Fast Ethernet 200 Mbps (full-duplex)

HARDWARE

- FCC Compliance, CE Mark
- Compliant with 32-bit PCI 2.1
- Realtek 8139 Chipset
- Link/Act LED

ENVIRONMENTAL

- Dimensions: 12 (W) x 13.3 (D) x 2.54 (H) cm (4.75 x 5.25 x 1 in.)
- Weight: 45.3 g (1.6 oz.)
- Operating temperature: 0 – 55°C (32 – 131°F)
- Storage temperature: 20 – 70°C (4 – 158°F)
- Operating humidity: 10 – 90%, non-condensing
- Storage humidity: 5 – 95%, non-condensing

SUPPORTED OS

- Windows 9x
- Windows 2000
- Windows 2003 Server
- Windows XP
- Windows XP64
- Windows NT
- Windows 3.11 / Windows for Workgroups
- MacOS
- Linux
- BeOS
- NOVELL 3.x, 4.x, 5.x, 6.x

PACKAGE CONTENTS

- Fast Ethernet PCI Network Card
- Setup diskette with quick install guide

For more information on INTELLINET NETWORK SOLUTIONS products, consult your local dealer or visit www.intellinet-network.com.



Copyright © INTELLINET NETWORK SOLUTIONS